



PN1.0、2.5MPa

PN≥4.0MPa

产品采用标准 Product adoption standards

结构形式 structure type	对夹升降式立式止回阀 Wafer lifting vertical check valve
设计标准 design standards	GB/T 12224
结构长度 Structure length	GB/T 15188.2
法兰连接 Flange connection	JB/T 79、GB/T9113、HB20592
试验和检验 Test and inspection	JB/T9092

注：阀门连接法兰及对焊端尺寸可根据用户要求设计制造

Note: The size of valve connecting flange and butt welding end can be designed and manufactured according to user requirements

主要零件材料 Material of main parts

序号 No.	零件名称 Part name	材质 Material
1	阀体 Body	WCB、CF8、CF8M、CF8C、CF3、CF3M
2	阀瓣 Disc	WCB、CF8、CF8M、CF8C、CF3、CF3M
3	弹簧 Spring	1Cr13、2Cr13、1Cr18Ni9Ti、0Cr18Ni12Mo2Ti
4	压板 Plate	WCB、CF8、CF8M、CF8C、CF3、CF3M
5	挡圈 Lock ring	4Cr13、60Si2Mn、1Cr18Ni9Ti、0Cr18Ni12Mo2Ti

主要外形尺寸 Main dimensions

型号 Model:H72H、H72Y

PN (MPa)	DN (mm)	尺寸 Dimensions(mm)		PN (MPa)	DN (mm)	尺寸 Dimensions(mm)		PN (MPa)	DN (mm)	尺寸 Dimensions(mm)	
		L	D			L	D			L	D
1.0 1.6	15	16	53	2.5	15	16	53	4.0	15	25	63
	20	19	63		20	19	63		20	31.5	74
	25	22	73		25	22	73		25	35.5	84
	32	28	84		32	28	84		32	40	90
	40	31.5	94		40	31.5	94		40	45	105
	50	40	109		50	40	109		50	56	115
	65	46	129		65	46	129		65	63	140
	80	50	144		80	50	144		80	71	150
	100	60	164		100	60	170		100	80	177
	125	90	194		125	90	197		125	110	213
	150	106	220	150	106	220	150	125	250		